



5-VMK-H 50
5-VFK-H 50
valve type with pilot valve


coaxial valve

type VMK-H 50 VFK-H 50



2/2 way valve externally controlled
pressure range PN 0-200 bar
orifice DN 50 mm
connection thread/flange
function valve normally closed symbol **NC**
valve normally open symbol **NO**



 Above stated body materials refer to the valve port connections that get in contact with the media only!

design pressure balanced, with spring return
body materials ① ② steel, galvanized
③ ⑤ without non-ferr. metals
④ steel, nickel plated ⑥ stainless steel
valve seat synthetic resin on metal
seal materials NBR PTFE, FPM, CR, EPDM

details needed for main valve


- orifice
- port
- function NC/NO
- operating pressure
- flow rate
- media
- media temperature
- ambient temperature
- type of actuation


details needed for pneumatic actuation

- nominal voltage
- type of protection
- actuation pressure range min/max
- low wattage coil, actuation pressure range 4-7 bar
- pilot valve type

details needed for hydraulic actuation

- actuation pressure range min/max
- hydraulic control valve function

 The valves' technical design is based on media and application requirements. This can lead to deviations from the general specifications shown on the data sheet with regards to the design, sealing materials and characteristics.

 If order or application specifications are incomplete or imprecise there exists a risk of an incorrect technical design of the valve for the required application. As a consequence, the physical and / or chemical properties of the materials or seals used, may not be suitable for the intended application.

■ specifications not highlighted are standard
■ specifications highlighted in grey are optional

general specifications

ports	VMK-H threads G 2	options	special threads
	VFK-H flanges PN 160/250		special flanges
function	NC		NO
pressure range	bar 0-200		
Kv value	m ³ /h 43,0		
vacuum	leak rate		< 10 ⁻⁴ mbar·l·s ⁻¹
pressure-vacuum	P ₁ ↔ P ₂		
back pressure	P ₂ > P ₁		available (max. 16 bar)
media			gaseous - liquid - highly viscous - gelatinous - pasty - contaminated
abrasive media			version available
damping	opening		
	closing by throttles on pilot valve		
flow direction	A ↔ B as marked		bi-directional upon request
switching cycles	1/min 100		
switching time	ms opening 100-3000 closing 100-3000		
media temperature	°C direct mounted pilot valve 60		remote mounted pilot valve outside temper.
ambient temperature	°C direct mounted pilot valve 50		ature range of media max.160°C
flush ports			available
leak ports			available
limit switches			inductive
manual override	via pilot valve		
approvals			LR/GL/WAZ
mounting			mounting brackets
weight	kg VMK-H 12,3 VFK-H 18,7		
additional equipment			upon request

electrical specifications

nominal voltage	U _n DC 24V	options	special voltage upon request
	U _n AC 230V 50 Hz		special voltage upon request
power consumption	DC 4,8 W		2,5 W
	AC pick up 11,0 VA holding 8,5 VA		
protection	IP 65 (P54) acc. DIN 40 050		
energized duty rating	ED 100%		
connection	plug acc. DIN EN 175301-803 form B, 4 positions x 90° / wire diameter 6-8 mm		
additional equipment	illuminated plug with varistor		
optional	M12x1 connector acc. DESINA		connector acc. VDMA
max. temperature	media 60°C		
	ambient 50°C		
explosion proof	EEx m II T5 nominal voltage U _n		direct current 24 V 3,25 W
	power consumption		alternating current 230 V 50 Hz 2,90 W

pneumatic specifications


actuation pressure range	bar 4-10	options	
air consumption	cm ³ /stroke 65		
cycle speed	main valve speed variable by throttles on pilot valve		
control	preferably 5/2-way pilot valve		
pilot valve interface	co-ax / NAMUR		ISO 1
actuator ports	2/4 G 1/8		G 1/4

hydraulic specifications

actuation pressure range	bar 10-30 / 30-60	options	
control	preferably 4/2-way control valve		
actuator ports	X/Y G 1/4		NPT 1/4

type VMK-H 50

function: **NC**
closed when not energized




constructive length	L1	L2	L3
standard	312	221	385
with 1/2 inductive limit switches	312	221	385
with force-feed lubrication nipple	312	221	385
with mechanical limit switches	-	-	-


flanges PN	DIN	øD	øk	ød
160	2638	195	145	26
250	2628	200	150	26

type VFK-H 50


function: **NO**
open when not energized



pneumatic actuation (separately)



5/2-way-pilot valve
flow rate 700 l/min
pressure range 3-10 bar G 1/8



5/2-way-pilot valve ISO 1
flow rate 700 l/min
pressure range 3-10 bar G 1/4

The application-specific layout relating to temperature, pressure conditions, switching behavior, media and its consistency may restrict the range of use or necessitate relevant modifications to materials used and seal arrangements.

Rights reserved to make technical alterations • Not responsible for printing errors • Detailed drawings can be obtained upon request